



92798 Cape Arago Hwy  
Coos Bay, OR 97420  
Phone (541) 888-3517  
Fax (541) 888-4846  
www.kksound.com

## TRINITY PREAMP

This 2-channel preamp is an extremely powerful yet small mixer in a belt clip box. It is designed for mixing a combination of a transducer and a microphone on one instrument to achieve the best possible transmission.

It offers volume, gain, bass, mid, and treble controls. The tone controls feature an extended range of up to +/- 20 dB, which exceeds many mixers on the market today. To keep the box as small as possible, the gain and tone controls are trim pots inside the unit (small potentiometers for adjustment with a supplied tiny screwdriver).

During performance, the musician can conveniently balance the two channels on the volume control knobs.

**Before first use, please insert a 9-volt battery. To switch the battery off, always unplug the MAIN/MIX OUT jack.**

### Setting up your Preamp:

1. Open the black screw and remove the lid. Insert 9-volt battery into the designated compartment.
2. There is a diagram for the internal trim pot controls on the inside of the lid. In the box you will find a little screwdriver for the adjustment of the trim pots. It is attached with a velcro fastener.
3. Connect your pickups to the stereo input via a **shielded ¼" stereo cable** (not supplied) and connect MONO/MIX OUT via a **mono ¼" guitar cable** into an amplifier.

If a second mono cable is inserted into MIC OUT, the channels will be carried separately. In other words, MIC OUT will carry only the microphone and MAIN/MIX OUT will carry only the pickup.

**A cable must be inserted in the MAIN/MIX OUT in order to switch on the battery power.**

4. Set your amp to a flat setting first. Adjust the gain trim pot the transducer channel. Adjust bass and treble trim pots to your preference.

### Technical Data:

Frequency response: 10-30,000 Hz  
Inputs: Instrument jacks 1 Mega Ohm  
Output: Instrument jack 10 Kilo Ohm  
Battery consumption: 3 Milli Amp

